



POCKET FILTER M5 – 360mm

Synthetic fiber filter made of first quality polyester fibres, offering medium filtration and dust holding performance.

TECHNICAL DATA

Frame type:	Galvanized 25mm
Depth pf pocket:	360mm
Reaction to fire:	M1 (DIN 53438)

APPLICATIONS

Pocket filters with medium and high filtration efficiency, normally used in the first or second filter stages or as a prefilter for cleanrooms process applications.

ISO Coarse 70%
(acc. ISO 16890)

M5
(acc. EN 779)

AVAILABLE DIMENSIONS:

Dimensions WxHxD (mm)	Number of pockets	Filter Area (m ²)	Nominal Air Flow (m ³ /h)	Initial pressure drop (Pa)
287x592x360	2	0,9	700	40
287x592x360	3	1,3	1 000	40
287x892x360	3	1,9	1 500	40
490x592x360	3	1,3	1 100	40
490x592x360	4	1,7	1 500	40
490x592x360	5	2,1	1 600	40
592x592x360	4	1,7	1 300	40
592x592x360	5	2,1	1 600	40
592x592x360	6	2,6	2 000	40
592x892x360	6	3,9	3 000	40

BENEFITS:

- Excellent resistance to the mechanical conditions of use
- Much larger filtration area than a flat filter
- High particle retention capacity (depending on the type of material chosen)
- High durability of the product
- Excellent resistance to humidity
- Dimensions according to the standard EN15805
- Quick and easy replacement